



# VABER INDUSTRIALE S.P.A.

PRODUZIONE ADESIVI E PRODOTTI CHIMICI INDUSTRIALI

Strada San Mauro, 203 I – 10156 Torino (ITALY)

Tel. +39 011273.44.32

Fax +39 011273.17.76 / +39 011 223.77.72

e-mail: info@vaber.it

## TECHNICAL DATA SHEET VABER MILLENNIUM LOGO TAPE 2001

**Date of release:** February 23, 2000

**Revision no.:** 5 **date:** 22.12.2009

**Approval:** R&D **Verified:** QMS

### 1. DESCRIPTION

VABER MILLENNIUM LOGO TAPE 2001 is a adhesive film ideal for positioning of parts in the assembly process.

Purposely designed for recovering logos and emblems of all types of vehicles. It is also ideal for positioning parts before final fixing or for fixing decorative and promotional items.

### 2. TECHNICAL PROPERTIES

ASPECT	: Acrylic Adhesive tape on silicone release paper
SIZE	: L300mm x h50mm
ADHESIVE FILM THICKNESS	: 0,04mm
TAPE THICKNESS	: 0,08mm
ADHESION ON STEEL	: 74 N /100 mm
APPLICATION TEMPERATURE	: +15°C ÷ +35°C

### 3. APPLICATION

Remove the emblem or logo from vehicle by cutting its original adhesive. Thoroughly clean the old foam on the logo with an antsilicon product and wait until completely dry. With antsilicone thoroughly clean the surface where the logo will be fixed.

Remove the liner from VABER LOGO TAPE 2001.

Place the logo with its back side in contact with the double-sided adhesive film of VABER LOGO TAPE 2001 and apply a uniform manual pressure.

When ready for transfer remove the logo from the adhesive strip. Place the logo on vehicle surface and apply a uniform manual pressure all over the logo.

### 4. PACKAGING

VABER LOGO TAPE 2001 is available in holders of 10 strips each.

### 5. STORAGE

VABER MILLENNIUM LOGO TAPE 2001 stored in its original package, in a dry and well ventilated place, at a temperature between +5°C and +35°C has a shelf life of 12 months from manufacturing date.

**6.NOTE**

The above information and our technical indications (both verbal and written or resulting from testing), in particular those that regard the applications and uses of our products, correspond to our best knowledge and experience; however, they do not constitute our warranty relative to final results or our responsibility deriving from any juridical relationship whatsoever.

In fact, considering the multiplicity of materials, supports, handling and storage conditions, as well as the conditions of production and utilization, the user, in function of his specific circumstances of use, must always preventively verify all the information and instructions reported above.

No assertion contained in this publication is to be considered authorization or suggestion to violate any industrial property rights of third parties.

©